RBX

Multiple Approved Single Jacket Rack Hose: Compact, lightweighted, easy-to-use

Built to balance performance and usability, RBX series combines a 100% polyester single jacket with a highly smooth TPU liner to ensure low friction loss, optimizing good performance for industrial or commercial use. Multi-certified by UL, ULC and NFPA, its compact, lightweight and pin-folded design make installation and deployment more convenient and efficient.



- **OUTER JACKET**
  Polyester
- **LINER**
  TPU
- **TEMPERATURE RANGE**
  -58°F to 158°F(-50°C to 70°C)
- **STANDARD LENGTH**
  50', 75' and 100'
- **STANDARD COLOR**
  uncoated

FEATURES

- Compact, lightweight design for easy transport and on-site use
- Pin-folded for quick installation & deployment
- Certifications: UL219, ULC S511, NFPA 1961
- Compatible with FM-approved NH/IPT threaded couplings (FM mandatory)
- Produced wihin ISO9001 quality management system
- Ultra-smooth TPU liner for low friction loss

TECHNICAL DATA

Nominal Size		Working Pressure		Test Pressure		Burst Pressure		Certification
inch	mm	psi	bar	psi	bar	psi	bar	
1-1/2″	38	250	17	500	34	750	51	c UL us
1-3/4″	45	250	17	500	34	750	51	FM APPROVED
2″	52	250	17	500	34	750	51	
2-1/2″	65	250	17	500	34	750	51	c UL us FM APPROVED

5ELEM
Web: en.5elem.com
Email: marketing@5elem.com