FireLock™ High-Pressure Butterfly Valve
Series 765 with Weatherproof Actuator – Supervised Open

10.80



1.0 PRODUCT DESCRIPTION

Available Sizes

- 2 – 12"/DN50 – DN300

Pipe Material

- Carbon Steel, Schedule 10 and Schedule 40. For use with alternative materials, contact Victaulic.

Maximum Working Pressure

- Up to 365 psi/2517 kPa/25 Bar

Application

- High-pressure butterfly valve with an approved weatherproof actuator housing for indoor and outdoor use.
- Designed for fire protection services only.
- Designed to be supervised open.
- Exclusively for use with pipe and Victaulic products that feature ends formed with the Victaulic Original Groove System (OGS) groove profile (see Section 7.1 Reference Materials).

Actuation Options

- Handwheel (2 – 12"/DN50 – DN300)

Available End Connections

- Victaulic Original Groove System (OGS)

2.0 CERTIFICATION/LISTINGS

c UL us LISTED

FM APPROVED

VdS G4090011

LPCB LPS 1185: Issue 3.1 Cert/LPCB Ref. 104j/02 846a/02

CE

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

 © 2026 Victaulic Company. All rights reserved.

2.1 CERTIFICATIONS/LISTINGS

Size		Approval/Listing Service Pressures				
		Series 765 Butterfly Valve				
Nominal inches DN	Actual Outside Diameter inches mm	cULus psi kPa	FM psi kPa	VdS psi kPa	LPCB psi kPa	CCC psi kPa
2 DN50	2.375 60.3	365 2517	365 2517	365 2517	365 2517	363 2500
2½	2.875 73.0	365 2517	365 2517	–	365 2517	–
DN65	3.000 76.1	365 2517	365 2517	365 2517	365 2517	363 2500
3 DN80	3.500 88.9	365 2517	365 2517	365 2517	365 2517	363 2500
	4.250 108.0	365 2517	365 2517	–	365 2517	–
4 DN100	4.500 114.3	365 2517	365 2517	365 2517	365 2517	363 2500
	5.250 133.0	365 2517	365 2517	–	365 2517	–
DN125	5.500 139.7	365 2517	365 2517	365 2517	365 2517	–
5	5.563 141.3	365 2517	365 2517	–	365 2517	–
	6.250 159.0	365 2517	365 2517	–	365 2517	–
	6.500 165.1	365 2517	365 2517	–	365 2517	363 2500
6 DN150	6.625 168.3	365 2517	365 2517	365 2517	365 2517	–
8 DN200	8.625 219.1	365 2517	365 2517	365 2517	365 2517	363 2500
10 DN250	10.750 273.0	365 2517	300 2068	–	365 2517	363 2500
12 DN300	12.750 323.9	365 2517	300 2068	–	365 2517	–

3.0 SPECIFICATIONS – MATERIAL

Body: Ductile iron conforming to ASTM A536, Grade 65-45-12.

End Face, 2 – 6"/DN50 – DN150: Ductile iron conforming to ASTM A536, Grade 65-45-12

Seal Retainer, 8 – 12"/DN200 – DN300: Ductile iron conforming to ASTM A536, Grade 65-45-12

Body Coating: Black alkyd enamel

Disc: Ductile iron conforming to ASTM A536, Grade 65-45-12, with electroless nickel coating conforming to ASTM B733

Seat: EPDM

Stems: 416 stainless steel conforming to ASTM A582

Stem Seal Cartridge: C36000 brass

Bearings: Stainless steel with TFE lining

Stem Seals: EPDM

Stem Retaining Ring: Carbon steel


Actuator:

- 2 – 8"/DN50 – DN200: Bronze traveling nut on a steel lead screw, in a ductile iron housing
- 10 – 12"/DN250 – DN300: Steel worm and cast iron quadrant gear, in a cast iron housing

 © 2026 Victaulic Company. All rights reserved.

4.0 DIMENSIONS

Series 765



Size		Dimensions										Approx. Weight (Each)
Nominal inches DN	Actual Outside Diameter inches mm	A inches mm	B inches mm	C inches mm	D inches mm	E inches mm	F inches mm	G inches mm	H inches mm	I inches mm	J inches mm	lb kg
2 DN50	2.375 60.3	4.25 108	2.28 58	6.41 163	–	–	4.00 102	4.22 107	4.50 114	0.68 17	2.12 54	8.2 3.7
2 ½	2.875 73.0	3.77 96	2.28 58	7.54 192	–	–	4.00 102	4.22 107	4.50 114	0.68 17	1.77 45	9.7 4.4
DN65	3.000 76.1	3.77 96	2.28 58	7.54 192	–	–	4.00 102	4.22 107	4.50 114	0.68 17	1.77 45	9.7 4.4
3 DN80	3.500 88.9	3.77 96	2.53 64	7.79 198	–	–	4.50 114	4.22 107	4.50 114	0.68 17	1.77 45	10.7 4.9
	4.250 108.0	4.63 118	2.88 73	8.81 224	–	–	5.50 140	4.22 107	4.50 114	0.68 17	2.20 56	14.0 6.4
4 DN100	4.500 114.3	4.63 118	2.88 73	8.81 224	–	–	5.50 140	4.22 107	4.50 114	0.68 17	2.20 56	14.0 6.4
	5.250 133.0	5.88 149	3.35 85	10.88 276	–	–	6.56 167	6.19 157	6.30 160	1.00 25	2.58 66	25.4 11.5
DN125	5.500 139.7	5.88 149	3.35 85	10.88 276	–	–	6.56 167	6.19 157	6.30 160	1.00 25	2.58 66	25.4 11.5
5	5.563 141.3	5.88 149	3.35 85	10.88 276	–	–	6.56 167	6.19 157	6.30 160	1.00 25	2.58 66	25.4 11.5
	6.250 159.0	5.88 149	3.84 98	11.38 289	–	0.41 10	7.52 191	6.19 157	6.30 160	1.00 25	2.58 66	28.7 13.0
	6.500 165.1	5.88 149	3.84 98	11.38 289	–	0.41 10	7.52 191	6.19 157	6.30 160	1.00 25	2.58 66	28.7 13.0
6 DN150	6.625 168.3	5.88 149	3.84 98	11.38 289	–	0.41 10	7.52 191	6.19 157	6.30 160	1.00 25	2.58 66	28.7 13.0
8 DN200	8.625 219.1	5.33 135	5.07 129	13.53 344	0.80 20	1.47 37	10.00 254	6.19 157	8.10 206	1.00 25	2.33 59	43.0 19.5
10 DN250	10.750 273.0	6.40 163	6.37 162	15.64 397	1.41 36	1.81 46	12.25 311	8.10 206	11.81 300	2.71 69	3.00 76	80.6 36.6
12 DN300	12.750 323.9	6.50 165	7.36 187	16.64 423	2.30 58	2.80 71	14.25 362	8.10 206	11.81 300	2.71 69	3.00 76	94.6 42.9

NOTE

- Optional ½"/15mm tap available for all sizes. Contact Victaulic for details.

 © 2026 Victaulic Company. All rights reserved.

5.0 PERFORMANCE

Series 765

This table expresses the frictional resistance of a Series 765 High-Pressure Butterfly Valve in equivalent feet/meters of straight pipe.

Size		Equivalent
Nominal inches DN	**Actual Outside Diameter** inches mm	Feet/m of pipe
2 DN50	2.375 60.3	6 1.8
2½	2.875 73.0	6 1.8
DN65	3.000 76.1	6 1.8
3 DN80	3.500 88.9	7 2.1
	4.250 108.0	8 2.4
4 DN100	4.500 114.3	8 2.4
	5.250 133.0	12 3.7
DN125	5.500 139.7	12 3.7
5	5.563 141.3	12 3.7
	6.250 159.0	14 4.3
	6.500 165.1	14 4.3
6 DN150	6.625 168.3	14 4.3
8 DN200	8.625 219.1	16 4.9
10 DN250	10.750 273.0	18 5.5
12 DN300	12.750 323.9	19 5.8

 © 2026 Victaulic Company. All rights reserved.

5.1 PERFORMANCE

Series 765

C_v values for flow of water at +60°F/+16°C through a fully open valve are shown in the table below. For additional details, contact Victaulic.

Formulas for C_v Values:

$$\Delta P = \frac{Q^2}{C_v^2}$$

$$Q = C_v \times \sqrt{\Delta P}$$

Where:
Q = Flow (GPM)
ΔP = Pressure Drop (psi)
C_v = Flow Coefficient

Formulas for K_v Values:

$$\Delta P = \frac{Q^2}{K_v^2}$$

$$Q = K_v \times \sqrt{\Delta P}$$

Where:
Q = Flow (m^3/hr)
ΔP = Pressure Drop (Bar)
K_v = Flow Coefficient

Size		Flow Coefficient
Nominal inches mm	**Actual Outside Diameter** inches mm	**Full Open** C_v K_v
2 DN50	2.375 60.3	170 147
2½	2.875 73.0	260 225
DN65	3.000 76.1	260 225
3 DN80	3.500 88.9	440 380
	4.250 108.0	820 710
4 DN100	4.500 114.3	820 710
	5.250 133.0	1200 1040
DN125	5.500 139.7	1200 1040
5	5.563 141.3	1200 1040
	6.250 159.0	1800 1560
	6.500 165.1	1800 1560
6 DN150	6.625 168.3	1800 1560
8 DN200	8.625 219.1	3400 2940
10 DN250	10.750 273.0	5800 5020
12 DN300	12.750 323.9	9000 7790

 © 2026 Victaulic Company. All rights reserved.

6.0 NOTIFICATIONS

⚠ WARNING



- **Read and understand all instructions before attempting to install any Victaulic products.**
- **Always verify that the piping system has been completely depressurized and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.**
- **Confirm that any equipment, branch lines, or sections of piping that may have been isolated for/during testing or due to valve closures/positioning are identified, depressurized, and drained immediately prior to installation, removal, adjustment, or maintenance of any Victaulic products.**
- **Wear safety glasses, hardhat, and foot protection.**

Failure to follow these instructions could result in death or serious personal injury and property damage.

- **These products shall be used only in fire protection systems that are designed and installed in accordance with current, applicable National Fire Protection Association (NFPA) standards, or equivalent standards, and in accordance with applicable building and fire codes. These standards and codes contain important information regarding protection of systems from freezing temperatures, corrosion, mechanical damage, etc.**
- **The installer shall understand the use of this product and why it was specified for the particular application.**
- **The installer shall understand common industry safety standards and potential consequences of improper product installation.**
- **It is the system designer's responsibility to verify suitability of materials for use with the intended fluid media within the piping system and external environment.**
- **The material specifier shall evaluate the effect of chemical composition, pH level, operating temperature, chloride level, oxygen level, and flow rate on materials to confirm system life will be acceptable for the intended service.**

Failure to follow installation requirements and local and national codes and standards could compromise system integrity or cause system failure, resulting in death or serious personal injury and property damage.

7.0 REFERENCE MATERIALS

Switch and Wiring


- The supervisory switch contains two single-pole, double-throw, pre-wired switches.
- Switches are rated:
  10 amps @ 125 or 250 VAC/60 Hz
  0.50 amps @ 125 VDC
  0.25 amps @ 250 VDC
- **Switches only supervise the valve in the "fully opened" position. The valve cannot be supervised in the "closed" position.**
- One switch has two #18 insulated wires per terminal, which permit complete supervision of leads (refer to diagrams and notes on this page). The second switch has one #18 insulated wire per terminal. This double circuit provides flexibility to operate two electrical devices at separate locations, such as an indicating light and an audible alarm, in the area that the valve is installed.
- A #14 insulated ground lead (green with yellow stripe) is provided. **NOTE:** The ground lead for older valve configurations may be solid green.

  Switch #1 = S1 For connection to the supervisory circuit of a UL Listed alarm control panel – The switch is open when the valve is in the "fully opened" position

  Switch #2 = S2 Auxiliary switch that may be connected to auxiliary devices, per the authority having jurisdiction

S1
- Normally Closed Contact: (2) Blue
- Common Contact: (2) Yellow

S2
- Normally Closed Contact: Blue with Orange Stripe
- Normally Open Contact: Brown with Orange Stripe
- Common Contact: Yellow with Orange Stripe



Switch contacts shown with the valve in the "FULLY OPENED" position

Only S1 (two leads per terminal) may be connected to the fire alarm control panel.

Connection of supervisory and auxiliary switches shall be in accordance with applicable sections of NFPA 72 and NFPA 70 (NEC).

 © 2026 Victaulic Company. All rights reserved.

7.1 REFERENCE MATERIALS

10.01: Regulatory Approval Reference Guide
10.75: FireLock™ Butterfly Valve Series 707C with Weatherproof Actuator – Supervised Closed
10.81: FireLock™ Butterfly Valve Series 705 with Weatherproof Actuator – Supervised Open
10.83: FireLock™ High-Pressure Butterfly Valve Series 766 with Weatherproof Actuator – Supervised Closed
25.01: Original Groove System (OGS) Groove Specifications
29.01: Terms and Conditions/Warranty
I-100: Field Installation Handbook
I-765/705: Series 765 and 705 Installation, Wiring, and Gear Operator Replacement Instructions
I-766/707C: Series 766 and 707C Installation, Wiring, and Gear Operator Replacement Instructions

User Responsibility for Product Selection and Suitability

Each user bears final responsibility for determining the suitability of Victaulic products for their end-use application, in accordance with industry standards, project specifications, and Victaulic's published performance, maintenance, and safety data, as well as all warnings and installation instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, warranty, installation instructions, or this disclaimer.

Installation

Always refer to and follow the Victaulic Installation Handbook or installation instructions for the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at victaulic.com.

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Intellectual Property Rights

No statement concerning the use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its affiliates, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries. Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.

Note

All products bearing a Victaulic trademark are manufactured by Victaulic or to Victaulic specifications. All products are to be installed only in accordance with the applicable Victaulic installation instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

 © 2026 Victaulic Company. All rights reserved.